

AHD-5702GW

Main Features

- 1.0MP. (1280x720 pixels) CMOS
- BNC interface, support for the general class of coaxial lossless transmission of up to 75-500 meters;
- Support AHD HD and SD analog switch output;
- Support IR-CUT switch, realize the day and night Monitor;



Specification

Model	AHD-5702GW
Main Sensor	High-performance processor
Image sensor	1/4 "CMOS image sensor
Effective Pixels	1280 X 720
Video Standard	Follow AHD and CVBS Standard
Video System	PAL/NTSC optional
Video Output	1CH AHD HD / CVBS Standard signal output (adjustable)
Video Frame Rate	PAL : 1280x720@25fps NTSC : 1280x720@30fps
Transmission Max Distance	Common 75-3 coaxial cable transmission of more than 500 Metres
Day-Night	Support the IR - CUT Automatically Switch
Infrared Lamp	2 Array LED
IR Distance	20-30M
Lens	4 mm / 6 mm optional
Mini Illumination	0.1 Lux (Color) / 0 Lux (Black) @ F1.2
Electronic Shutter	4/25s~1/45,000s
OSD Menu	Optional
White Balance	Automatic / Manual
Backlight Compensation	Closed / Low / Middle / High / Higher
Strong Inhibition	Support
Color / Material	White
Working Voltage	DC12V 1A
Power Consumption	4W±10%
Work Environment	-20°C_55°C
Product/Package Size	CAMERA/195*102*98mm
Carton Size/Quantity	540*420*530mm
Water Resistance	IP66
Installation Environment	Outdoor day and night